

RTV1100			
SPECIFICATIONS			
		RTV1100	
ENGINE	RTV1100W Orange		
	RTV1100R Realtree™ Camouflage		
Make and Model	Kubota D1106-E2-UV		
Type	3 Cylinders, Water cooled 4-Cycle, Diesel, OHV		
Displacement	68.5 cu in (1123 cc)		
Horsepower	24.8 hp (18.5 kW)@3000		
Fuel Capacity	7.9 U.S. gal (30 liters)		
Transmission	Variable hydro transmission (VHT)		
Max. Traveling Speed	25 mph (40 km/h)		
Wheels, drive system	Rear 2WD or 4WD selection		
Differential lock	Standard; foot operated with mechanical holder		
Gear selection	Hi-Med-Lo range forward, neutral, reverse		
Brakes Front / Rear	Wet-disc brake		
Parking brake	Rear wheel, hand lever		
Steering	Hydrostatic power		
Suspension Front / Rear	Independent, MacPherson strut-type / semi-independent, DeDion axle w/leaf springs and shock absorber		
DIMENSIONS	Length	128.4 (3262)	
	Width	66.5" (1688 mm)	
	Height, overall	82.8" (2104 mm)	
	Front tread centers	45.3" (1150 mm)	
	Rear tread centers	46.5" (1180 mm)	
	Wheelbase	77.4" (1965 mm)	
	Ground Clearance Front Axle	8.1" (205 mm)	
	Rear Axle	7.5" (190 mm)	
	Turning diameter	26.2' (8.0 m)	
Max. rolling weight (Towing Cap.)	1300 lbs (590 kg)		
Payload capacity	1631 lbs (740 kg)		
Weight	2469 lbs (1120 kg)		
CARGO BED	Width	52" (1320 mm)	
	Length	46.7" (1180 mm)	
	Depth	11.4" (290 mm)	
	Volume	16 cu ft (0.455 cm)	
	Bed height (unloaded)	32.3" (820 mm)	
	Cargo bed load	1102 lbs (500 kg)	
Sound level, operator ear	83 dB(A) @ Max. engine speed w/no load		
TIRES	Front	25x10-12 ATV, 6 Ply	25x10-12 ATV, 6 Ply
		25x10-12 HDWS, 6 Ply	25x10-12 HDWS, 6 Ply
		25x12-12 ATV, 4 Ply	-
	Rear	25x11-12 ATV, 6 Ply	25x11-12 ATV, 6 Ply
		25x10-12 HDWS, 6 Ply	25x10-12 HDWS, 6 Ply
		25x12-12 TURF, 4 Ply	-
Front Guard	Std.		
Hydraulic bed lift	Std.		
Speedometer	Std.		

** Realtree™ is a registered trademark of Jordan Outdoor Enterprises Ltd.

The company reserves the right to change the above specifications without notice.

The values in "Ground clearance" and "Weight" are those of the machine equipped with tires in the table above.